

CARINT SLP 1508 CI FLEXO PRESS

Number of colours: 8
Print possibilities: 8+0
Fast sleeve change
4 motor per deck CNC position system
Web width: 1050mm
Print width: 1000mm
Minimum print repeat: 320mm
Maximum print repeat: 600mm
Unwinder: semi automatic turret
Maximum reel diameter unwinder: 800mm
Rewinder: automatic turret
Maximum reel diameter rewinder: 800mm
Drying: gas burners 100.000kcal/h
Corona treatment: AFS G40S
Web guides: Bst before and after printing
Viscosity control: Fasnacht FKR S4
Print sleeves: 152 Rossini Everstat
Printing repeat with sleeves: 320-600mm
Gearing: 5mm
Infeed driven nip roller
Plc Siemens S7
Thermo regulator for CI drum and chill roller
Hydraulic lifting device for reels loading/unloading
Sleeve change system outside the machine

Printing sleeves as follows for mandrels diameter: 105, 158mm 8 x 360, 380, 400, 420mm
for mandrels diameter 105, 158mm 8 antistatic carriers diameter 127, 440mm printing sleeves 8 x 430, 440, 450, 460, 480, 500mm for mandrels diameter 105, 158mm antistatic carriers diameter 149, 722mm

Printing sleeves: 8 x 520, 540, 560, 580mm
for mandrels diameter 105, 158mm antistatic carriers diameter 181, 553mm

Printing sleeves: 8 x 600, 620, 640, 660, 680mm
No 19 sets each of 8 for a total of 152 gears having the following specs: 360, 380, 400, 420, 430, 440, 450, 460, 480, 500, 520, 540, 560, 580, 600, 620, 640, 660, 680mm
Printing speed: up to 300mt/min

General

Year of manufacture: 2004
Location: Europe
Reference: R55434

Price:

Link to Website www.polygraphica.com

